

- 1
- 2
- 3
- 4
- 5
- 6
- 7
- 8
- 9
- 10
- 11
- 12
- 13
- 14
- 15
- 16
- 17
- 18
- 19
- 20
- 21
- 22
- 23
- 24
- 25
- 26
- 27
- 28
- 29
- 30
- 31
- 32
- 33
- 34
- 35
- 36
- 37
- 38
- 39
- 40
- 41
- 42
- 43
- 44
- 45
- 46
- 47
- 48
- 49
- 50
- 51
- 52
- 53
- 54
- 55
- 56
- 57
- 58
- 59
- 60
- 61
- 62
- 63
- 64
- 65
- 66
- 67
- 68
- 69
- 70
- 71
- 72
- 73
- 74
- 75
- 76
- 77
- 78
- 79
- 80
- 81
- 82
- 83
- 84
- 85
- 86
- 87
- 88
- 89
- 90
- 91
- 92
- 93
- 94
- 95
- 96
- 97
- 98
- 99
- 100

An interface of an application program is identified by parsing the source code of the application program to identify meta information, and the meta information and a link pointing to an original location of the meta information within the application program are stored in a repository. A user may then be allowed to query the repository to determine which source files and which interfaces comprise the application program. Responsive to the query, a new source file is constructed which contains the interfaces comprising the application program. The new source file and a link pointing to a location of the new source file are also stored in the repository. A meta language document is constructed which contains a description of the application program interfaces to enable a connector building tool to build an interface to the application program.